

United States District Court,
N.D. California, San Jose Division.

HEWLETT-PACKARD COMPANY, Hewlett-Packard Development Company, L.P.,
Plaintiffs.

v.

EMC CORPORATION,
Defendant.

EMC Corporation,
Counterclaimant.

v.

Hewlett-Packard Company, Hewlett-Packard Development Company, L.P., Compaq Computer Corporation,
Counterdefendants.

No. C 02-04709 JF

June 23, 2004.

Amy Kathleen Vanzant, Heller Ehrman LLP, Menlo Park, CA, Chris Landgraff, Mark E. Ferguson, Reeghan W. Raffals, Barlitt Beck Herman Palenchar & Scott, Chicago, IL, Michael Kenneth Plimack, Heller, Ehrman, LLP, San Francisco, CA, for Plaintiffs.

Christopher Ryan Ottenweller, Orrick, Herrington & Sutcliffe, Menlo Park, CA, Lisa C. Ward, Orrick Herrington & Sutcliffe LLP, Irvine, CA, for Defendant. Steven Derringer, Barlitt Beck Herman Palenchar & Scott, Chicago, IL, for Plaintiffs/Counterdefendants.

I. Neel Chatterjee, Orrick Herrington & Sutcliffe LLP, Menlo Park, CA, Michael C. Spillner, Orrick Herrington & Sutcliffe LLP, Menlo Park, CA, Todd Michael Briggs, Quinn Emanuel Urquhart Oliver & Hedges LLP, Redwood Shores, CA, Robert T. Haslam, III, Heller Ehrman LLP, for Defendant/Counterclaimant. Reeghan W. Raffals, Barlitt Beck Herman Palenchar & Scott LLP, Chicago, IL, for Counterdefendants.

Court-Filed Expert Resumes

ORDER CONSTRUING CLAIMS OF UNITED STATES PATENTS NO. 4,821,184, NO. 5,237,658, NO. 5,247,618, NO. 5,315,602, NO. 5,325,497, NO. 5,390,327, NO. 5,544,347, NO. 5,659,801, NO. 5,917,253, NO. 6,122,756, NO. 6,269,453, AND NO. 6,356,979; AND DENYING MOTION TO PRECLUDE HP FROM ASSERTING NEW CLAIM CONSTRUCTION POSITIONS

JEREMY FOGEL, District Judge.

On April 5 and 6, 2004, the Court held a hearing for the purpose of construing key disputed terms in the

claims of United States Patents No. 4,821,184 ("the '184 patent"), No. 5,237,658 ("the '658 patent"), No. 5,247,618 ("the '618 patent"), No. 5,315,602 ("the '602 patent"), No. 5,325,497 ("the '497 patent"), No. 5,390,327 ("the '327 patent"), No. 5,544,347 ("the '347 patent"), No. 5,659,801 ("the '801 patent"), No. 5,917,253 ("the '253 patent"), No. 6,122,756 ("the '756 patent"), No. 6,269,453 ("the '453 patent"), and No. 6,356,979 ("the '979 patent"). After consideration of the arguments and evidence presented by the parties and the relevant portions of the record, the Court construes the disputed terms as set forth below. In light of its construction of the claims and in order to achieve the most accurate construction possible, the Court will deny Defendant's motion to preclude Plaintiffs from asserting new claim construction positions. FN1

FN1. In connection with the claim construction hearing, Defendant also moved to disqualify Plaintiffs' expert witness, Dr. Randy Katz. The Court intends to deny the motion and will set forth its reasoning in a separate order to be issued at a later date. Additionally, because it has not considered the declaration of Stephen J. Wallach, the Court declines to address Defendant's objections thereto.

I. BACKGROUND

On September 30, 2002, Plaintiffs and Counterdefendants ("HP") filed suit against Defendant and Counterclaimant ("EMC"), alleging infringement of several of the claims of HP's '658, '618, '602, '253, '453, '979, and '327 patents. EMC counterclaimed alleging that HP infringed several of the claims of EMC's '184, '497, '347, '801, and '756 patents. The '184 patent incorporates by reference U.S. Patent No. 4,455,602 ("the '5602 patent"), and much of the Court's analysis of the '184 patent is derived from the '5602 patent. The patents generally relate to devices, systems, and methods for storing or backing up electronic information on memory systems. The parties seek damages, declaratory judgment, an injunction, treble damages for willful infringement, attorneys' fees, and other relief.

HP's asserted patent claims will be described generally first. A general description of EMC's asserted claims will follow. These descriptions are not meant to be read as part of the Court's claim construction but rather are provided to put the claim construction in context.

A. HP's Asserted Claims

The '618 patent contains method and apparatus claims for transferring data between storage media. Storage media are materials within a storage device on which data is recorded or represented (for example, magnetic disks). The purpose of the patented invention is to protect against loss or corruption of data by maintaining multiple copies of the data. Such multiple copies are called a "shadow set." In the main claim, a host processor issues a command for data on a first storage medium to be copied to a second storage medium. The copies are part of the shadow set. Whenever one copy is altered, all copies in the shadow set similarly are altered. The key claim also includes a limitation in which access of the host processor to the data in the shadow set is "stalled" if the files in the shadow set are in the process of being copied among the various storage media.

The purpose of the invention claimed in the '658 patent is to provide an improved method of connecting several processors (or computers) to several memory storage arrays. The storage array permits redundant copying of data to several distinct media, thus allowing recovery if one medium fails. The prior art dealt only with connecting processors to multiple storage devices. The invention claimed in the '658 patent allegedly is novel because processors are connected to multiple storage *arrays*, each of which has several storage devices for redundant storage. The change from single storage devices (such as disk drives) to arrays

presented a challenge with respect to the method by which the devices are connected. Accordingly, the inventors claim a "switching network means" that allows any of several processors to connect to any of several memory storage devices. Each array has at least one "array controller" through which the array is connected to the switching network means. The specification describes the switching network means as an "N x N cross-point switch or an N x N multi-stage switch." The internal architecture of the switching network means can be complex.

The '253 patent focuses on the power supply for the system. Its goal is to provide a means by which the processor and memory devices retain power even if one of the power supplies fails, in other words, a redundant physical power supply system. Such a system reduces the potential for data loss and computer down time. For example, two AC mains may supply power to two "power supplies," which then provide DC power to the computer system. If one of the AC mains fails, the other AC main very rapidly provides power to both of the power supplies "without any substantial loss in transfer of line voltage." This occurs through an "automatic" "switching apparatus." In the preferred embodiment, there are two AC mains and three power supplies.

The '602 patent relates to the process of transferring data from a host processor to redundant memory storage devices. It describes a "redundant array of inexpensive disks" ("RAID"), on each of which data are stored in a block ("data blocks"). Each disk has a redundant copy of a data block. The set of redundant copied blocks is called a "stripe." For each set of data blocks, a "parity data block" also is generated, and the parity block is part of the stripe. "Parity data" is information about the copies that enables the system to reconstruct the data in a data block if the data are lost or corrupted.

Associated with the storage devices is a "memory buffer cache," from which data are written to the disk drives and which a host computer can access more quickly than it can access the disk drives. Host "logical I/O" requests (input/output requests) store data to the memory buffer cache and host "physical I/O" requests store data to the disk drives. Cache storage is more vulnerable to loss or corruption, while disk drive storage is "non-volatile."

The purpose of the claimed invention is to generate new parity data for a stripe with as few "I/O requests" as possible whenever there is a change in a data block. Using an I/O request, the system must read data or parity blocks from the disk drive. For example, if there are five data blocks in the disk drives with the same copy and the system alters data relating to one of those blocks, there are two ways to alter the parity data for the stripe. First, each data block may be read from the disk drives, requiring four I/O requests. Alternatively, the old parity data block and an old data block may be read from the disk drive and then compared to the new data block, thus requiring only two I/O requests. If all of the data blocks already are in the memory buffer cache, then no additional I/O requests would be needed. The claimed invention assesses how to alter a stripe of blocks using the fewest I/O requests.

The '453 patent relates to methods for restoring data in a RAID-based memory storage system if one of the disks fails and for restoring the RAID array itself after the failed disk is replaced. Here, it is noted that "striping" has the further advantage of speeding up access to data from the memory because the data might be accessed simultaneously from five disks. Data in the stripe are broken into "chunks." A chunk is a group of consecutively numbered data blocks placed logically or physically consecutively on a single disk. A "block" is the smallest quantity of data that can be read or written to a disk. Each "stripe" consists of chunks written across multiple disks in the array.

The RAID-4 and RAID-5 systems include a "parity system." A "parity block" contains parity information-error correction codes to reconstruct data if a disk fails or a data block otherwise becomes unavailable-for a group of one or more data blocks. A "parity chunk" is one chunk in a strip that contains parity information for the other chunks in the strip. In RAID-4 systems, the parity information is stored on a single disk. In RAID-5 systems, it is stored over all of the disks in the array. When a disk fails, it is restored using the redundant data and the parity data.

The purpose of the claimed invention is to allow continuous use of the system before the lost or failed disk is restored, that is, while the memory is in a non-redundant state. The system regenerates the lost data from the other data chunks and the parity chunk and then *writes the restored data over the parity information*. In this way, all of the data blocks are available, but the memory is no longer redundant (this is the configuration of a RAID-0 array). This process is called "folding." The patent also discloses a method for restoring the array to its redundant state, or "unfolding." If the replacement disk contains parity information, that information is determined from the data chunks on the other disks and written to the new disk. If it contains data, then data are read from the disk that originally contained the parity data and written on the replacement disk, and parity data are then determined from the resulting data blocks and stored on the other disks in the appropriate locations.

The '327 patent is related to the '453 patent. Its purpose is to carry out the process just described while allowing the system to remain operational; that is, the array remains accessible to applications. It does this by keeping track of the state of a data block. Specifically, a group of "array state bits" indicate whether a data block that is targeted by an application is in one of the following states: normal, folding, fully folded, or unfolding. The system uses this information to maximize access to the memory array without compromising its integrity.

The '979 patent describes a system including a memory storage system that is accessible to multiple host computing systems. The goal of the invention is to permit selective access to data in the storage system because different host computers and operating systems may conflict when attempting to access the storage system, thus corrupting the system or limiting communication ability. Data are organized in the storage system as "logical units" ("LUNs"). The invention permits certain hosts to access only certain LUNs by using a "configuration table," which is stored in memory and which governs the interactions between LUNs and host computers. Different types of information may be stored in the configuration table.

B. EMC's Asserted Claims

The '801 patent relates to a computer system with peripheral components (such as a memory storage device, printers, and video devices) that have their own processors and software programs that control their operation. The goal of the claimed invention is to update the software in the peripheral components (this software also is known as "microcode") by delivering it from the central computer. The process begins when the computer sends an "initiator peripheral device command" to the peripheral device, which responds by entering a "waiting state," in which it is ready to receive the new microcode. The computer then sends a "transfer peripheral device command," which contains the new microcode. Finally, the peripheral device replaces the old microcode with the new.

The '497 patent discloses a method for labeling a "logical set" of memory. A logical set is a set of physical disk drives functioning as one logical drive. Each logical set has a "global identifier" and each member of the set has a "membership signature ." The global identifier and membership signatures are substantially

similar. If one of the disks fails or is taken out of the memory system and replaced, it no longer would have the same membership signature because it may no longer correspond to the other members of the logical set. In this way, members of a logical set are identified and changed members are excluded from the logical set.

The '184 patent incorporates by reference the hefty '5602 patent. It discloses a data organization method whereby data are organized into "objects," which are identified by "unique identifiers" ("UIDs"). "[D]ata is addressed by means of a logical address which specifies the UID of the object containing the data and the offset of the data in the object." '184:3/6-9. In this way, a computer may access data stored in "universal logical memory."

The '756 patent relates to a self-diagnosing and self-correcting computer system. The computer system automatically tests itself, identifying any flawed components, and then "de-configures" the flawed components without impairing the system as a whole, although the system continues to operate in a degraded state until the component is replaced. A replacement step is not included in the claims.

The '347 patent discloses another system for backing up data. A computer with a local primary memory storage system stores data on that primary storage system. The primary storage system has a controller that receives data from the computer and controls their storage. The primary storage controller is connected via high speed communications link to a secondary memory storage controller in a secondary memory storage system that is geographically distinct from the first. The primary storage controller sends a copy of the data to the secondary storage controller, which stores a back-up copy at the geographically distinct location. The secondary storage controller sends an indication to the first controller that it has received the data and that the data are valid.

II. APPLICABLE LAW

Claim construction is a question of law to be decided by the Court. *Markman v. Westview Instruments, Inc.*, 52 F.3d 967, 979 (Fed.Cir.1995), *aff'd*, 517 U.S. 370, 116 S.Ct. 1384, 134 L.Ed.2d 577 (1996). When assessing claim meaning the Court must ask what a person having ordinary skill in the art would understand the claim language to mean at the time of the invention. *DeMarini Sports, Inc. v. Worth, Inc.*, 239 F.3d 1314, 1324 (Fed.Cir.2001). The Court must look first to the intrinsic evidence of record: the patent claims, the specification, and, if in evidence, the prosecution history. *Vitronics Corp. v. Conceptronic, Inc.*, 90 F.3d 1576, 1582 (Fed.Cir.1996). The general rule is that claim terms are to be given their ordinary and accustomed meaning. *Johnson Worldwide Assocs. v. Zebco Corp.*, 175 F.3d 985, 989 (Fed.Cir.1999). However, the patentee may choose to be its own lexicographer and may use terms in a manner other than their ordinary meaning so long as the special definition is stated clearly in the patent specification or file history. *Vitronics*, 90 F.3d at 1582. The specification acts as a dictionary when it expressly defines terms used in the claims or when it defines terms by implication, and is considered to be "the single best guide to the meaning of a disputed term." *Id.*

In most situations, analysis of the intrinsic evidence will resolve any ambiguity regarding a disputed claim term. *Id.* at 1583. In such circumstances, the Court may not rely on extrinsic evidence. *Id.* However, where the intrinsic evidence is ambiguous as to a disputed term or the scope of the invention, the Court may turn to extrinsic evidence such as expert testimony, prior art, and inventor testimony. *Id.* at 1584. Such evidence may be used to help the Court understand the claims but may not be used to vary or contradict the claim language. *Id.*

Technical treatises and dictionaries may be used at any stage of the claims construction process. In fact, such sources likely should be used at the initial step of reading the claim language itself, because "[c]onsulting the written description and prosecution history as a threshold step in the claim construction process, before any effort is made to discern the ordinary and customary meanings attributed to the words themselves, invites a violation of [Federal Circuit] precedent counseling against importing limitations into the claims." *Texas Digital Sys., Inc. v. Telegenix, Inc.*, 308 F.3d 1193, 1204 (Fed.Cir.2003), *cert. denied*, 538 U.S. 1058, 123 S.Ct. 2230, 155 L.Ed.2d 1108 (2003). In determining the ordinary meaning of a term, the Court may consult technical treatises and dictionaries publicly available at the time the patent is issued "at any time in order to better understand the underlying technology and may also rely on dictionary definitions when construing claim terms, so long as the dictionary definition does not contradict any definition found in or ascertained by a reading of the patent documents." *Vitronics*, 90 F.3d at 1584 n. 6; *see also* *Teleflex, Inc. v. Ficoso N. Am. Corp.*, 299 F.3d 1313, 1325 (Fed.Cir.2002). The intrinsic evidence and dictionaries must be considered together: because "words often have multiple dictionary definitions, some having no relation to the claimed invention, the intrinsic record must always be consulted to identify which of the different possible dictionary meanings of the claim terms in issue is most consistent with the use of the words by the inventor." *Texas Digital Sys., Inc.*, 308 F.3d at 1203.

As a general claim construction principle, limitations found only in the written description of the specification of a patent should not be imported or read into a claim. *In re Donaldson*, 16 F.3d 189, 195 (Fed.Cir.1994); *Laitram Corp. v. NEC Corp.*, 163 F.3d 1342, 1347 (Fed.Cir.1998). However, in some instances limitations from the specification may be imported into a claim. In such instances, the Court "looks to whether the specification refers to a limitation only as part of less than all possible embodiments or whether the specification read as a whole suggests that the very character of the invention requires the limitation be a part of every embodiment." *Alloc Inc. v. Int'l Trade Comm'n*, 342 F.3d 1361, 1370 (Fed.Cir.2003). Where "the specification makes clear at various points that the claimed invention is narrower than the claim language might imply, it is entirely permissible and proper to limit the claim." *Id.* A second exception applies if a claim is expressed in "means plus function" or "step plus function" format in accordance with 35 U.S.C. s. 112, para. 6, which states:

An element in a claim for a combination may be expressed as a means or a step for performing a specified function without the recital of structure, material, or acts in support thereof, and such claim shall be construed to cover the corresponding structure, material, or acts described in the specification and equivalents thereof.

The first step in construing a means-plus-function limitation is to identify the function of the limitation recited in the claim. *Texas Digital Sys., Inc.*, 308 F.3d at 1208. The next step is to identify the corresponding structure set forth in the written description necessary to perform that function. *Id.* "Structure disclosed in the specification is 'corresponding' structure only if the specification or prosecution history clearly links or associates that structure to the function recited in the claim." *Id.* (quoting *B. Braun Med., Inc. v. Abbott Labs.*, 124 F.3d 1419, 1424 (Fed.Cir.1997)). Corresponding structure is limited to that necessary to perform the recited function and its structural equivalents. *Micro Chemicals, Inc. v. Great Plains Chem. Co.*, 194 F.3d 1250, 1257-58 (Fed.Cir.1999).

III. DISCUSSION

A. Disputed terms of claim 1 of the '618 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.

A method of transferring data between two storage media in a **shadow set** of storage media accessible by one or more **host processors** for I/O requests, said method comprising the steps of:

A. receiving a command from one of said **host processors**, said **command specifying data to be transferred** from a first said storage medium to a second said storage medium;

B. transferring said data specified in said command from said first storage medium to said second storage medium in a series of subtransfers, each of said subtransfers transferring a portion of said specified data; and

C. processing one or more I/O requests received from said **host processors** for access to said **shadow set** by, for each received I/O request:

a. implementing said I/O request if said I/O request does not involve a section of said **shadow set** currently involved in one of said subtransfers; and

b. stalling said I/O request if said I/O request involves a section of said **shadow set** currently involved in one of said subtransfers, and implementing said I/O request when said one of said subtransfers has been completed.

1. "host processor"

HP asks the Court to construe this term as "a processor that controls or accesses all or part of a user application network." EMC proposes: "a processor in a host computer that can issue read or write requests to the first and second storage media." HP argues that "the [parties'] only disagreement concerns whether or not the processor must reside in something called a "host computer." Plaintiffs' and Counterclaim Defendants' Corrected Opening Claim Construction Brief on Key Terms ("HP's Opening Brief"), p. 6 n. 4. As defined by the claim, a host processor is a processor that is capable of sending commands to a storage medium or requests for access that are received by a shadow set. HP's proposal adds a reference to a "user application network." EMC's proposed language adds the requirement that the host processor reside in a host computer.

According to HP, the dictionary meaning of "host processor" is "a processor that controls all or part of a user application network." HP's Opening Brief, p. 6; Declaration of Christopher D. Landgraff ("Landgraff Decl."), Separate Appendix, vol. 1, p. 0195. However, the claim language does not include reference to a "user application network," and it is not clear what a "user application network" for the purposes of the claim would be, although it could be the claimed system as a whole. Instead, the claim language refers to commanding a storage medium and accessing a shadow set. Similarly, while the written description includes diagrams suggesting that a host processor may be part of a "host," the claim language does not include reference to a "host computer." The claim language simply has no location limitation, and while the word "host" may limit "processor," it need not do so by geography. Looking at all of the dictionary definitions provided by the parties, it is clear that a "host processor" is part of a network or system and that it controls or accesses other parts of the system. *See id.* The plain language of the claim indicates that "host processor" refers to a specific type of processor, one that sends commands to the memory aspects of the system. The claim language does not specify the physical location of the host processor.

Accordingly, the appropriate construction of the "host processor" as used in claim 1 is "a processor that can send a command to a storage medium or requests for access that are received by a shadow set."

2. "command specifying data to be transferred"

HP asks the Court to construe this term as "an order identifying data to be transmitted from a first storage medium to a second storage medium." EMC proposes: "command specifying the data to be transferred by reference to the starting block numbers on the source and target and the quantity of data to be copied."

According to the plain language of the claim, a "command specifying data to be transferred" is a command sent from a host processor that specifies which data are transferred from a first storage medium to a second storage medium. HP's proposed construction thus adheres generally to the plain language of the claim. EMC, on the other hand, seeks to import limitations from the specification. HP argues that to "specify" is to "identify," while EMC seeks to include in the definition the method by which "specifying" occurs, thus not only defining the term but also importing a method limitation. The parties agree that at a minimum "specifying" means "identifying, naming, or stating explicitly or in detail." Joint Claim Construction and Prehearing Statement ("JCCPS"), Ex. B. This is consistent with the plain language of the claim and is sufficient for purposes of claim construction. There is no ambiguity that requires reference to a particular method or embodiment for identifying explicitly or in detail. Nor is there any apparent reason for exchanging the word "transferred" for "transmitted" and "order" for "command" as proposed by HP.

Accordingly, the appropriate construction of "command specifying data to be transferred" as used in claim 1 is "a command sent from a host processor that identifies, names, or states explicitly or in detail which data is transferred from a first storage medium to a second storage medium."

3. "shadow set"

HP asks the Court to construe this term as: "Two or more copies of data that may be located in different places. If a change is made to any copy, that change is reflected in the others." EMC proposes: "Two or more identical copies of data that has been written to a storage medium, and that are treated as one from the host processor's point of view. If a change is made to any copy, that change is automatically made to the other copies."

At first glance, the plain language of the claim appears to indicate that a "shadow set" is composed of *storage media* that are accessible by one or more host processors for I/O requests. The claim states that data are transferred between different storage media within a shadow set and that the storage media are accessed by a host processor. The shadow set thus would comprise defined storage media that contain the data to be transferred within the defined storage media. However, in the context of the claim, the language "shadow set of storage media" could mean a limited set consisting of part of the storage media that contain a shadow set. In other words, a shadow set could be composed of *data* that are moved between storage media, in which case the identity of the storage media would be irrelevant. Indeed, the parties characterize a shadow set as "copies of data" either written to a storage medium or located in different places. Thus, it is unclear from the claim language itself whether the shadow set is composed of storage media or data.

The specification indicates that "shadow set" refers to data. For example, the "preferred embodiment is described in connection with a system for establishing and maintaining one or more duplicate or 'shadow' copies of stored data." '618:1/27-30. Similarly, "systems have been developed that create multiple copies of stored data, usually on separate storage devices Such multiple copies are known as the shadow set."

'618:1/42-47. However, the parties each seek to add an additional limitation relating to whether all copies in a shadow set are identical or reflect each other and whether a change to one copy results in a change on all copies. The specification provides that "[i]n a shadow set, typically data that is stored in particular blocks on one member of the shadow set is the same as data stored in corresponding blocks on the other members of the shadow set." '618:1/47-50. Thus, because the shadow set by definition contains redundant copies of the data, each copy must be the same, and necessarily, any change in one copy correspondingly is made in other copies within the shadow set. If a change in one copy is not made to the others, then that copy no longer can be a member of the shadow set. Dictionary definitions support this interpretation. For example, "shadow" is partially defined as "a link between duplicate objects.... If a change is made in either the duplicate or the original, the change takes effect in the other as well." Landgraaf Decl., Separate Appendix, vol. 1, p. 0197 (IBM Dictionary of Computing).

EMC proposes adding additional limitations, requiring the copies of data to be "treated as one from the host processor's point of view" and updated "automatically." However, nothing in the claim language or specification supports or requires limiting the claim in this way.

Accordingly, a person of ordinary skill in the art would have understood the "shadow set" term of claim 1 to mean: "Copies of data located on one or more storage media. If a change is made to any copy, that change is reflected in the others."

B. Disputed terms of claims 1 and 14 of the '658 patent.

1. "switching network ... for establishing a communications link "

The text of claim 14 is set forth below with the key disputed term highlighted in bold type.

A multiprocessor computer system comprising:

- a. a plurality of processing units;
- b. at least one data storage array system, each having at least one array controller;
- c. at least one **switching network**, coupled to the plurality of processing units and to at least one array controller of at least one data storage array system, **for establishing a communications link** between at least one selected processing unit and at least one data storage array system.

HP asks the Court to construe this term as: "A component or set of components to which multiple nodes can attach and that selectively enables giving, receiving, or exchanging of information, signals and/or data among attached nodes." EMC proposes: "A circuit switch, not contained within a data storage array system, that is capable of establishing a dedicated path from any input node of the switch to any output node of the switch." The critical dispute between the parties is whether the term "broadly covers both 'circuit switching' and 'packet switching' " or whether it is limited to "circuit switching." EMC's Response to HP's Opening Claim Construction Brief ("EMC's Response"), p. 12.

The plain language of the claim indicates that a switching network establishes a communications link between the processing units and the data storage array system by coupling to them and that a plurality of processing units is coupled to a switching "network." Thus, there must be multiple connection points between the processing units and the switching network. This conclusion is consistent with HP's

construction.

Nothing in the claim language limits "switching network" to a particular type of "switch." The switching network only need be coupled to the processing units and the data storage array system. Thus, both circuit and packet switching could occur within the switching network. In fact, the specification provides support for multiple types of switching. For example, the specification states that it does not limit the type of switching to the disclosed embodiments, ' 658:4/44-47, Figure 2 appears to depict at least direct circuit switching, and Figure 3B depicts "multi-stage switch architecture," which consists of a matrix of "selectors" through which signals are transferred. In Figure 3B, each signal may travel through multiple selectors to its final destination.

Although the specification does not support importation of the limitation suggested by EMC, it does provide clarification as to the intended meaning of "switching network." That is, a switching network must be capable of coupling any node to any other node. *See, e.g.*, '658:5/25-26 & 5/38-40. Dictionary definitions are consistent with this view. For example, "switch" is defined as "a network infrastructure component to which multiple nodes attach," and "network" is defined as "an interconnect that enables communication among a collection of attached nodes." *See Landgraff Decl., Separate Appendix, vol. 2, pp. 0324-26 (A Dictionary of Storage Networking Terminology)*. A person of ordinary skill in the art would understand a switching network to mean a component or a set of components to which multiple nodes can attach and that selectively enables transferring of information, signals, or data among the attached nodes.

EMC also contends that the switching network must not be located within the data storage array system. However, nothing in the intrinsic evidence supports such a limitation. In the prosecution history cited by EMC, the patentee distinguished the invention from the prior art on the ground that a switching network was used between the processors and the disk storage array system, while the prior art described the use of a switch between the array controller and the storage units. *See Landgraff Decl., Separate Appendix, vol. 2, p. 0285*. The distinction does not concern the *physical* location of the switch but rather where the switch is placed *logically* in the system in relation to each component. Logically, the switching network must be between the processors and the disk storage array system.

Accordingly, the Court construes this term as "a component or set of components to which multiple nodes can attach and that selectively enables transferring of information among attached nodes ."

2. "switching network means ... for establishing a communications link"

The text of claim 1 is set forth below, with the key disputed terms highlighted in bold type.

A multiprocessor computer system comprising:

a. a plurality of processing units;

b. at least one data storage array system, each having at least one array controller;

c. **switching network means**, coupled to the plurality of processing units and to at least one array controller of at least one data storage array system, **for establishing a communications link** between at least one selected processing unit and at least one data storage array system.

This claim is expressed in means plus function format, and the Court therefore construes it pursuant to 35 U.S.C. s. 112, para. 6. HP defines the function as "establishing a communications link between at least one selected processing unit and at least one data storage array system." Because HP's proposal is consistent with the plain language of the claim, the Court will adopt it.

HP defines the corresponding structures as found in "Figs. 2, 3A, 3B, 4; Col. 5:1-6:45." *See* HP's Opening Brief, p. 13. HP thus asks the Court to construe this term as: "A component or set of components to which multiple nodes can attach and that selectively enables giving, receiving, or exchanging of information, signals and/or data among attached nodes, having structures that are the same as or substantially equivalent to those found in Figures 2-4 and described at Columns 5:1-6:45." EMC defines the structure more narrowly, proposing: "A circuit switch, not contained within a data storage array system, that is either a cross-point or multi-stage switch that is capable of establishing a dedicated path from any input node of the switch to any output node of the switch, as described in Col. 5, ll 4-51 and shown in Figs. 3A and 3B."

EMC's argument is persuasive in part. The structures described in Figures 3A and 3B and in Column 5, lines 4 through 67 clearly are associated with the function of establishing a communications link between at least one selected processing unit and at least one data storage array system. *See* Texas Digital Sys., Inc., 308 F.3d at 1208. In contrast, while Figures 2 and 4 show a "switching network," they do not provide the structure of the "switching network," but instead show the "switching network" as part of the overall system configuration. Similarly, the text in the written description corresponding to those figures does not clearly link the function of the switching network means to its structure.

When the patent specification describes multiple embodiments, each of those embodiments may be claimed pursuant to 35 U.S.C. s. 112, para. 6. *Serrano v. Telular Corp.*, 111 F.3d 1578, 1583 (Fed.Cir.1997). The structures described in Figures 3A and 3B and in Column 5, lines 4 through 67 generally "may be of any suitable N x N type, capable of directly coupling any node to any other node." The figures and written description also describe specifically "an N x N cross-point switch or an N x N multi-stage switch" as disclosed in Column 5, lines 7 through 51. The written description additionally indicates that the switching network may comprise fiber optic or wired links and is fault-tolerant and that the switch may be a dual switching network. Accordingly, the structure of the "switching network means for establishing a communications link" is "any suitable N x N type switching network, capable of directly coupling any node to any other node in addition to the specific embodiments disclosed in Figures 3A and 3B and Column 5, lines 7 through 67." FN2

FN2. Because it need not determine in the context of claim construction whether Figure 3B (a multi-switch) includes the possibility of "packet switching," the Court will reserve judgment on the issue. The parties may describe the disclosed structure further in the infringement analysis.

C. Disputed terms of claims 1 and 12 of the '253 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.

A circuit comprising:

(a) first and second energized AC feed circuits;

(b) **first and second receiving circuits connected to and energized by, respectively, the first and second feed circuits;** and,

(c) first switching apparatus which automatically connects the second feed circuit to the first receiving circuit in the event the first feed circuit is de-energized, whereby both the first and second receiving circuits are energized by the second feed circuit without any **substantial loss in transfer of line voltage.**

The text of Claim 12 is set forth below, with the key disputed terms highlighted in bold type.

A redundant electrical system comprising:

(a) first and second energized AC energy sources;

(b) first and second energy transfer circuits connected to and energized by, respectively, the first and second energy sources; and,

(c) a first relay connected to and energized by the first energy source for automatically disconnecting the first energy source from the first transfer circuit and automatically connecting the second energy source to the first transfer circuit in the event the first energy source is de-energized, whereby both the first and second transfer circuits are energized by the second energy source without any **substantial loss in the transfer of line voltage.**

1. "first and second receiving circuits connected to and energized by, respectively, the first and second feed circuits"

HP asks the Court to construe this term as follows: "The first receiving circuit is connected to and receives electricity or is currently capable of receiving electricity from the first feed circuit and the second receiving circuit is connected to and receives electricity or is currently capable of receiving electricity from the second feed circuit." EMC proposes: "The first receiving circuit is physically connected to and is receiving electricity from the first AC feed circuit. At the same time, the second receiving circuit is physically connected to and is receiving electricity from the second AC feed circuit."

Essentially, the parties dispute the meaning of the phrase "energized by." HP asks the Court to construe "energized by" as "receives electricity or is currently capable of receiving electricity." EMC argues that the correct construction is "is receiving electricity." Under EMC's proposal, claim 1 would not protect an invention in which the receiving circuit is not currently receiving electricity from its respective AC feed circuit.

The meaning of "energized by" in the claim language is ambiguous. The Court thus turns to the specification for clarification. The written description indicates that the "AC mains [are] feed circuits which provide voltage," '253:3/9-10, and that "when both AC mains are energized, all three power supplies receive voltage," '253:3/34-36. Thus, for the purposes of the claim, a person of ordinary skill in the art would understand "energize" to mean "to provide voltage to." "Energized by" thus generally means "receives voltage from."

The claim states that a receiving circuit is "connected to and energized by" a feed circuit. Accordingly, a receiving circuit is "connected to and receives voltage from a feed circuit." Nothing in the claim language

indicates that a receiving circuit must *constantly* receive voltage from the same feed circuit. Indeed, the claim language as a whole describes a situation in which both receiving circuits are energized by the second feed circuit "in the event the first feed circuit is de-energized." The specification also suggests that a feed circuit might not always provide voltage to a receiving circuit. For example, an AC main might fail, in which case it could not provide voltage to a receiving circuit. *See, e.g.*, '253:3/29, 4/6-14, & 4/34-45. While the prosecution history shows that the patent examiner found the term "capable of being energized" indefinite, the meaning of "energize" in the context of the claim and the specification must include scenarios in which the receiving circuit is not always energized by the same feed circuit. There is no evidence in the prosecution history that the patentees stated that a certain feed circuit must continually energize a receiving circuit. Rather, the evidence suggests that they rewrote the claims to clarify that "the receiving circuits of claim 1 ... are *connected to and energized by* the respective feed circuits." *See Landgraff Decl., Separate Appendix, vol. 3, p. 0386.* In other words, they did not intend to claim continual energizing, but rather to clarify which circuit energizes the receiving circuit for the purposes of subparagraph (b) of claim 1.

EMC also contends that, based on the claim language and the prosecution history, the two receiving circuits must be energized "at the same time." While it is true that the patentees argued that their "invention keeps at least two load circuits energized at all times, regardless of whether one energy source fails or not," *id.* at 0388, nothing in the disputed claim language requires that the two be energized at the same time by distinct AC feed circuits. The claim language merely indicates that the two receiving circuits are connected to and energized by feed circuits. As noted, the receiving circuits may not always be energized by their respective feed circuits. Although EMC's argument initially appears consistent with subsection (b) of the claim and the relevant prosecution history, it nonetheless does not make sense to require the two receiving circuits to be energized at the same time by *respective* feed circuits because, if a receiving circuit ceases receiving voltage from a feed circuit, "automatic switching capability" permits the invention to keep at least two receiving circuits energized "at all times" through a *different, functioning* feed circuit. *Id.*

The Court thus construes this term as: "The first receiving circuit is connected to and receives electricity or is capable of receiving electricity from the first feed circuit and the second receiving circuit is connected to and receives electricity or is capable of receiving electricity from the second feed circuit."

2. "substantial loss in transfer of line voltage"

HP asks the Court to construe this term as: "The voltage at the destination of the transfer is substantially less than that at the source." With respect to claim 1, EMC proposes: "A substantial loss in AC line voltage when switching from the first AC feed circuit to the second AC feed circuit. A loss in AC line voltage of 3dB or more is a substantial loss." With respect to claim 12, EMC proposes: "A substantial loss in AC line voltage when switching from the first AC energy source to the second AC energy source. A loss in AC line voltage of 3dB or more is a substantial loss."

Subparagraphs (c) of claims 1 and 12 indicate that the receiving circuits of claim 1 and the transfer circuits of claim 12 are energized without substantial loss from a single feed circuit or energy source, respectively, when compared to the amount of voltage transfer received from both feed circuits or energy sources. That is, each receiving or transfer circuit must be energized in substantially the same amount after failure of one of the two feed circuits or energy sources. Accordingly, for the purposes of this term, the voltage signal at the final destination (either the receiving circuits or the transfer circuits) prior to the de-energization of the first feed circuit or first energy source is compared to the voltage signal at the same final destination after

the deenergization of the first feed circuit or first energy source.

The parties dispute whether there may be a "substantial loss in the transfer of line voltage" *during* the switch. Clearly, the object of the claimed invention is to prevent loss of energy to a circuit if an AC feed line or energy source fails. The specification describes an example of a switch that can achieve this object: for example, the "switching speed of relay 65 must be less than about one signal cycle of the AC main (i.e., about 20 ms), so that continuity of the signal is maintained for the power supply after switching AC mains." '253:3/60-63. Thus, consistent with the claim language, the specification describes a device in which transfer of line voltage signal is never substantially lost, either during or after the switch, as measured against the extent to which the circuit was energized prior to the switch. Although there may be energy loss during the switch, that loss is not substantially less with respect to the final destination—because of the nature of the AC signal—than what would have occurred if there had been no switch. Although the Court concludes that the claim language indicates that substantial loss is measured after "the first feed circuit [or energy source] is de-energized" rather than after the switch is made, it must be noted that there may be energy loss associated with the switch as long as such loss occurs during a specific portion of the AC cycle so that there is not substantial loss of voltage at the final destination when compared to the voltage received prior to the deenergization of the AC energy source.

EMC also seeks to add a limitation defining "substantial loss" as a loss in AC line voltage of 3 dB or more. The term "substantial" is ambiguous. The specification does not expressly define—indeed it does not discuss at all—the concept of "substantial loss." In this context, the written description instead consistently describes the invention as providing for *redundant* sources of energy should a source fail. For example, various embodiments of the invention are described, in which "power supplies ... remain energized for supplying power to the system," '253:4/4-5, the circuit "always suppl[ies] AC current to the off (third) power supply ..., regardless of a loss of either of the redundant AC mains," '253:4/12-14, "no matter which AC main fails, all three power supplies remain powered for system 60 via the other live redundant main," '253:4/32-34, if a first AC main fails, a second AC main "provid[es] continued voltage," '253:4/43, and the system may "retain energized both power supplies ... in the event of failure of either AC main," '253:4/48-49.

While the written description never quantifies the energy loss resulting from the use of "redundant" energy supplies, the patentee discloses an invention in which the circuits may function normally as if a source of energy had not been lost. Thus, it is clear that, whatever precise quantity the parties wish to assign to the term "substantial loss in the transfer of line voltage," it must have significance with respect to the functioning of the device. That is, for "substantial loss" to occur, the output of the electrical system or functioning of whatever device is powered by the claimed invention must be impaired by loss of the redundant energy source. Examples of such impairment are described in the specification. For example, loss of energy could result in "loss of data and down time upon failure." '253:1/14-15. Accordingly, in the claimed invention, the output of the electrical system is not affected by a failed AC line because, through the use of redundancies, there is not a substantial loss in the transfer of line voltage.

EMC argues that substantial loss must be quantified as "3 dB" because a reference discussing a signal loss of up to 3 dB was presented to the patent examiner during prosecution. However, this reference merely showed that a 3 dB signal loss is substantial, a characterization with which HP agrees. Plaintiffs' and Counterclaim Defendants' Reply Brief on Key Terms, p. 19. It did not preclude an argument that something less than 3 dB also is substantial. EMC does not explain what "3 dB" means in the context of the present invention. Because the reference to the prior art in the prosecution history did not address the issue of quantifying "substantial loss" and because the meaning of "3 dB" is ambiguous, the Court finds the

prosecution history unhelpful in providing additional clarification.

Accordingly, the Court construes this term as: "Loss of receipt of energy-as measured by the voltage at the final destination (either the receiving circuits or the transfer circuits) after the de-energization of the first feed circuit or first energy source compared to the voltage at the same final destination prior the de-energization of the first feed circuit or first energy source-sufficient to impair the proper functioning of whatever device is powered by the claimed invention during and after loss of the redundant energy source."

D. Disputed terms of claim 1 of the '602 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.

An apparatus for generating parity data for a plurality of disk drives, each of the plurality of disk drives divided into a plurality of blocks, the plurality of blocks further organized into a plurality of stripes, each of the plurality of stripes including one block from each of the plurality of disk drives, one of the blocks of each stripe storing parity data generated from the data stored in the other blocks of the stripe, the apparatus comprising;

memory means for storing data, said memory means partitioned into blocks compatible with the block structure of the plurality of disk drives;

means for identifying an updated memory block storing data to be written to one of the plurality of disk drives;

means for identifying a predetermined stripe, said predetermined stripe including a disk block to be overwritten by said updated memory block;

first means for determining the number of I/O requests required to aggregate in said memory means all of the data, except the parity data, of said predetermined stripe;

second means for determining the number of I/O requests required to aggregate in said memory means said block to be overwritten and the parity block of said predetermined stripe; and

means for choosing said first means OR said second means to perform said I/O requests by choosing the means which requires the fewest number of I/O requests to aggregate in said memory means the blocks of said identified stripe necessary to generate the parity data of said predetermined stripe.

1. "memory means"

Because this term is expressed in means plus function format, the Court must construe it pursuant to 35 U.S.C. s. 112, para. 6. HP characterizes the function as "memory" and asks the Court to construe the term as: "A unit of a computer that preserves data for retrieval having structures that are the same as or substantially equivalent to those found in Figure 1 at 11, 40 and described at Col. 2:44-52." FN3 EMC contends that the function is "storing data" and the corresponding structure is "cache (40) connected to a host computer (10) through a system bus (30), and located between the host computer (10) and the disk device (20)."

FN3. HP acknowledges that it erred in referring to number 11 and that number 40 is the correct structure.

The function of the "memory means" clearly is data storage. The corresponding structure in the specification that is associated or linked with this function is described in Figure 1 and in Column 2, lines 44 through 52. The memory means that is partitioned into blocks is shown in Figure 1 as structure (40) and also is known as the "cache."

While the parties agree that the underlying structure is the cache (40), *see, e.g.*, Transcript of April 6, 2004 Hearing, 328:5-6, they disagree as to whether the structure has a location limitation. EMC argues that the block diagram shows that the cache must be located between the host computer and the disk device and that it must be connected through a bus. However, nothing in the claim or specification supports this argument. Figure 1 is not a drawing of a likeness of the system as it would exist in three-dimensional space; rather, it is a schematic representation that shows how the components are connected *logically*. Figure 1 equally might indicate that the disk device is located between the host computer and the cache. Nor does the written description contain an unambiguous indication of how the components are located physically with respect to each other. For example, it states that the host computer is connected to the disk device via a communication bus, '602:2/49-50, and then states that the computer system includes a cache that also is connected to the system bus, '602:2/51-52. Accordingly, it would be inappropriate for the Court to include a location limitation in the identification of the underlying structure.

The Court therefore construes this term as having the function of "data storage." The corresponding structure is the "cache" as shown in Figure 1 and described in Column 2, lines 51-52.

2. "first means for determining the number of I/O requests required to aggregate in said memory means all of the data, except the parity data, of said predetermined stripe"

This term also is expressed in means plus function format, and the Court thus must construe it pursuant to 35 U.S.C. s. 112, para. 6. The function of the "first means" is "determining the number of I/O requests required to aggregate in the memory means all of the data, except the parity data, of the predetermined stripe."

HP contends that the corresponding structures: "are the same as or substantially equivalent to those found in Figure 4 and described at Col. 4:21-26; Col. 5:10-15; 23-26; 34-52." EMC argues that the corresponding structure is "a host computer (10) programmed to perform the algorithm described at column 5, lines 34-52 and illustrated in figure 4." The parties dispute only whether the computer *system* generally or the "host" component of the computer system alone performs the function. While the direct references to Figure 4 in the specification discuss the "computer" or the "system," and not the "host," *see* '602:5/10, 5/36, & 5/42, the written description does not state what part of the system performs the function. Elsewhere, however, the written description states that the "computer system 1 includes a central processor unit or 'host' 10 having primary temporary data storage, such as memory 11," FN4 '602:2/46-48; *see also* '602:Figure 1, and that the "host" is the part of the system that issues I/O requests, '602:2/58.

FN4. The host clearly includes more than a "central processor unit." For example, it includes memory 11. However, the host does not include the cache 40 or disk drive 20. *See* '602:Figure

Moreover, identifying the structure as the system rather than the host standing alone may lead to invalidation of the claim on grounds of indefiniteness because the patent does not describe how the "computer system," as opposed to the "host," would achieve the stated function. Controlling Federal Circuit authority holds that:

The definiteness requirement is to ensure that the claims are written in such a way that they give notice to the public of the extent of the legal protection afforded by the patent, so that interested members of the public, e.g., competitors of the patent owner, can determine whether or not they infringe.

All Dental Prodx, LLC v. Advantage Dental Prods., Inc., 309 F.3d 774, 779-80 (Fed.Cir.2002). In order to avoid a finding of indefiniteness, the Court must thoroughly "attempt to understand the meaning of a claim [in order] to resolve material ambiguities." Id. at 780. Because the claim at issue is a means plus function claim, the Court must look to the specification for clearly associated structure. The specification clearly describes only a system in which the "system" includes a host that issues the I/O requests. Accordingly, the corresponding structure is "the host in the computer system 1 programmed to perform the algorithm described in Column 5, lines 10 through 15, 23 through 26, and 34 through 52 and illustrated in Figure 4."

3. "second means determining the number of I/O requests required to aggregate in said memory means said block to be overwritten and the parity block of said predetermined stripe"

Once again, this term is expressed in means plus function format, and the Court construes it pursuant to 35 U.S.C. s. 112, para. 6. The Court construes the function of the "second means" as "determining the number of I/O requests required to aggregate in the memory means said block to be overwritten and the parity block of the predetermined stripe."

HP contends that the corresponding structures: "are the same as or substantially equivalent to those found in Figure 5 and described at Col. 4:27-36; Col. 5:15-19; 26-30; 5:53-6:18." EMC argues that the corresponding structure is "a host computer (1) programmed to perform the algorithm described at column 5, line 53 through column 6, line 18 and illustrated in figure 5." The parties again dispute whether it is the computer system generally or solely the "host" component of the computer system that performs the function.

As discussed above, while it is true that the direct references to Figure 5 in the specification discuss the "computer" or the "system," and not the "host," *s ee* '602:5/57, 5/60, 5/63, 7/1, & 7/7, the written description states that the "computer system 1 includes a central processor unit or 'host' 10 having primary temporary data storage, such as memory 11," '602:2/46-48; *see also* '602:Figure 1, and that the "host" is the part of the system that issues I/O requests, '602:2/58. Moreover, as noted above, identifying the structure as the system rather than the host could result in a determination that the claim is indefinite.

Accordingly the Court construes the corresponding structure as "the host in the computer system 1 programmed to perform the algorithm described in Column 5, lines 16 through 19, Column 5, lines 26 through 30, and Column 5, line 53 through Column 6, line 18 and illustrated in Figure 5."

4. "I/O request"

HP asks the Court to construe this term as: "A directive to any operation, program, or device that transfers data to or from a computer." EMC proposes: "A request issued by a host computer, such as a read or write request, to transfer data."

Although the claim indicates that I/O requests are used to aggregate data in the memory means, the meaning of the term itself is not clear from the claim language alone. The specification clarifies that I/O requests are used both to write new data to the cache and disk device and to organize and distribute data to those structures. For example, "the host 10 issues I/O requests, such as reads and writes, to transfer data between memory 11 and the disk device 20 via the bus 30 and cache 40." '602:2/58-60. "Host 10 'logical' I/O write requests store the new data in the cache 40, and the 'physical' I/O write requests transfer the data from the cache 40 to the disk drives." '602:3/6-8. "With striping, a host I/O request distributes the data to be transferred across the disk drives." '602:3/62-64. The subsequent portions of the written description describe how the computer system determines and attempts to minimize the number of required I/O requests. Thus, the specification indicates that I/O requests are issued from the host 10, and the computer system attempts to minimize the number of required requests.

A location limitation is not required for the purpose of construing the term. This is not a means plus function term, and the claim language does not include the location from which I/O requests are issued. Instead, the claim is directed toward organizing the memory of the system, and it does not identify the particular computer components that direct such organization. Definitions from dictionaries support this view. "I/O" is defined as the

process of moving data between a computer system's main memory and an external device or interface such as a storage device, display, printer, or network connected to other computer systems. I/O is a collective terms for *reading*, or moving data into a computer system's memory, and *writing*, or moving data from a computer system's memory to another location.

Landgraff Decl., p. 0565. An "I/O request" is a "request by an application to read or write a specified amount of data." EMC's Response, Ex. A (Dictionary of Storage Networking Terminology). Just as in the claim language, nothing in the dictionary definitions limits which components of the computer system may contain such applications or issue such requests. In contrast, consistent with the definitions, the claim language indicates that I/O requests serve to organize data; that is, data are moved among the system's components regardless of the origin of the I/O request.

Accordingly, I/O requests are "commands, such as reads and writes, used to transfer data among various components or portions of the components of the computer system."

E. Disputed terms of claim 1 of the '453 patent.

1. "fully folded array"

The text of claim 1 is set forth below with the key disputed term highlighted in bold type.

In a storage system having $n+1$ disks arranged in a RAID array, a plurality of data blocks arranged into a plurality of data chunks, a plurality of parity blocks arranged into a plurality of parity chunks, each parity block associated with n data blocks in n data chunks, said data chunks and said parity chunks distributed over said $n+1$ disks, one of said parity chunks and all of said data chunks that are associated with said parity chunk forming a strip, a method of reorganizing said data chunks when one of said $n+1$ disks fails, comprising the steps of:

detecting the failure of one of said $n+1$ disks;

determining if said failed disk contains all parity chunks;

if said failed disk contains all parity chunks, terminating said method;

if said failed disk contains at least some data chunks, then for each strip containing a data chunk located on said failed disk, regenerating the data of said data chunk located on said failed disk and writing said regenerated data onto said parity chunk associated with said data chunk of said failed disk to form a **fully folded array**.

HP asks the Court to construe this term as: "An organization of a RAID array essentially that of a RAID-0 organized array except that the disk on which a chunk of data is stored may be unconventional." EMC proposes:

A "fully-folded array" is an array of disks that results after the completion of a "folding" process. The 'folding' process begins after a disk in the array fails. The data of the failed disk is reconstructed and stored onto the parity chunks of the active disks in the array. The "folding" is complete when all of the parity chunks of the active disks have been overwritten with the reconstructed data of the failed disk.

The claimed invention enables continuing access to stored data even when a storage disk has failed. It does so by reconstructing the failed data and writing them onto portions containing parity data on other disks. When this occurs, the data are accessible, but the disk storage system no longer has parity data and thus no longer has redundant data storage. Any data that are lost thereafter cannot be reconstructed or regenerated. In this state, the data storage device is a "fully folded array." The user can continue to access the data until a replacement disk is added, at which time the data are "unfolded" and restored to their redundant state.

While the plain language of the claim does not explain the meaning of "fully folded array," the specification provides a sufficient explanation for purposes of claim construction. For example, the summary of the invention clearly defines a fully-folded array as one in which the level of organization of data is non-redundant and which contains regenerated data from a failed disk in the place of previously existing parity data corresponding to that regenerated data. *See* '453:2/35-49.

HP's proposed construction is accurate in the sense that it restates an explanation from the specification. However, it does not take advantage of the full description provided; the Court's construction seeks to define fully the terms proposed by HP. While the fully-folded array is defined partially by characteristics obtained from the process of folding, EMC improperly attempts to import the process by which the data are fully folded into the construction. At the same time, the fully-folded array contains regenerated data in places that previously contained parity data; the Court will include this property in its construction without importing method or process limitations.

Accordingly, the Court construes this term as "a memory storage array in which the level of organization of data is non-redundant and which contains regenerated data from a failed disk in the place of previously existing parity data corresponding to that regenerated data."

F. Disputed term of claims 1 and 7 of the '327 patent.

1. "array state bits"

The text of claim 1 is set forth below with the key disputed term highlighted in bold type.

A method of on-line reorganization of data in a storage system having $n+1$ disks arranged in a RAID array when one of said disks falls while preserving concurrent access to said array by a user application, each of said disks in said storage system having a plurality of data blocks, a plurality of parity blocks, each parity block associated with n data blocks, a plurality of groups of parity block state bits, each group of parity block state bits indicating that said associated parity block contains parity information or data or the contents are undefined, and a group of **array state bits** indicating the condition of the array as "normal," "folding," "fully folded" or "unfolding," said method comprising the steps of:

- (a) receiving a read request from said user application to read a targeted data block;
- (b) interrogating said **array state bits** to determine the condition of said array;
- (c) if said **array state bits** indicate said array is in said "normal" state, then proceeding with a read operation;
- (d) if said **array state bits** indicate said array is in said "folding" state, then proceeding with a "folding" read operation;
- (e) if said **array state bits** indicate said array is in said "fully folded" state, then proceeding with a "fully folded" read operation; and
- (f) if said **array state bits** indicate said array is in said "folding" state, then also proceeding with a deliberate process to complete said reorganization concurrently with user application access to said array.

The text of claim 7 is set forth below, with the key disputed term highlighted in bold type.

A method of on-line reorganization of data in a storage system having $n+1$ disks arranged in a RAID array when one of said disks fails while preserving concurrent access to said array by a user application, each of said disks in said storage system having a plurality of data blocks, a plurality of parity blocks, each parity block associated with n data blocks, a plurality of groups of parity block state bits, each group of parity block state bits indicating that said associated parity block contains parity information or data or the contents are undefined, and a group of **array state bits** indicating the condition of the array as "normal," "folding," "fully folded" or "unfolding," said method comprising the steps of:

- (a) receiving a write request from said user application to write to a targeted data block;
- (b) interrogating said **array state bits** to determine the condition of said array;
- (c) if said **array state bits** indicate said array is in said "normal" state, then proceeding with a write operation;
- (d) if said **array state bits** indicate said array is in said "folding" state, then proceeding with a "folding" write operation;
- (e) if said **array state bits** indicate said array is in said "fully folded" state, then proceeding with a "fully

folded" write operation; and

(f) if said **array state bits** indicate said array is in said "folding" state, then also proceeding with a deliberate process to complete said reorganization concurrently with user application access to said array.

HP asks the Court to construe this term as: "Bits indicating the state of the array as a whole." EMC proposes: "Bits stored on each disk in a RAID array that indicate the condition of the RAID array as being 'normal,' 'folding,' 'fully-folded,' and 'unfolding.' "

The claim language reveals that array state bits may indicate the condition of the array as normal, folding, fully folded, or unfolding. Nevertheless, a list of things that an object may indicate does not necessarily define the object. Indeed, the specification acknowledges that array state bits identify other information as well. For example, "[i]n the preferred embodiment, two array state bits identify the missing or replacement member disk and two additional array state bits identify the state of the array." '327:11/67-12/2. Similarly, "[t]he state information for the array as a whole includes the following: (a) Identity of the missing or replacement member disk and (b) Array state. The array state includes (a) 'normal,' ... (b) 'folding,' ... (c) 'fully folded,' ... and, (d) 'unfolding.'" '327:11/50-57. Accordingly, looking to the specification to help define the term without importing limitations, the Court concludes that "array state bits" contain information relating to the identity of a missing or replacement disk and the state of the array.

EMC's proposal further requires the array state bits to be "stored on each disk in a RAID array." However, nothing in the claim or the specification indicates that a location limitation is necessary for proper claim construction.

Accordingly, the Court construes this term as "bits that identify either the missing or replacement member disk or the state of the array."

G. Disputed terms of claims 1 and 3 of the '979 patent.

The text of claim 1 is set forth below with the key disputed term highlighted in bold type.

A storage system capable of selectively presenting logical units to two or more host computing systems, the storage system comprising:

one or more persistent storage devices arranged as logical units;

an array controller controlling and coordinating the operations of said persistent storage devices;

a memory accessible by said array controller; and

a **configuration table** stored in said memory, said **configuration table** containing one or more entries governing one or more interactions between the logical units and the two or more host computing systems, wherein said **configuration table** contains an access field entry for each logical unit, said access field entry indicating if a particular logical unit can be permitted by the array controller to communicate with a particular one of said host computing systems.

The text of claim 3 is set forth below with the key disputed terms highlighted in bold type.

The system of claim 1, wherein said **configuration table** contains a **host mode** entry for each logical unit, said **host mode** entry indicating if a particular logical unit should communicate with a particular one of said host computing systems using a predetermined **host mode**.

1. "configuration table"

HP asks the Court to construe this term as: "A data structure used to organize information regarding the assignment of certain operating parameters of the storage system." EMC proposes: "A table organized on a logical unit by-logical unit basis containing, for each logical unit, one or more data fields related to the logical unit."

The meaning of "configuration table" is unclear from the language of claim 1, which indicates that a "configuration table" may contain "entries governing one or more interactions between the logical units and the two or more host computing systems" and "an access field entry for each logical unit." Claim 3 includes a further potential characteristic of a configuration table: "a host mode entry for each logical unit."

The written description states that "the configuration tables store information relating to which host connection a particular logical unit should communicate with, any LUN numbers offsets employed by the logical unit to communicate with a particular host, and any special 'host modes' employed by the array controller in communicating with a particular host." '979:3/64-4/2. Thus, the claim language and the specification indicate that the configuration table contains data that govern the interactions between logical units and host computing systems. The specification and the claims include examples of the specific types of data contained in a configuration table, including "access fields," "offset fields," and "host mode fields." *See e.g.*, '979:4/3-36 & 5/21. However, such examples need not be imported as limitations for the purposes of defining this particular term. Indeed, claim 1 explicitly does not include an "offset field entry" limitation or a "host mode entry" limitation (these are found in dependent claims 2 and 3). Using the doctrine of claim differentiation as a guide to claim construction, *Laitram Corp. v. Rexnord, Inc.*, 939 F.2d 1533, 1538 (Fed.Cir.1991), it would be inappropriate for the Court to specify particular types of entries in its construction of "configuration table."

HP's proposal also is ambiguous and potentially is too broad. Under HP's construction, the configuration table would contribute to organization of "information regarding the assignment of certain operating parameters of the storage system." However, the claim and the specification indicate that the configuration table is limited to data that govern the interactions between the logical units and the host computing systems. It is unclear from the intrinsic evidence what "assignment of certain operating parameters" means. According to a dictionary cited by HP itself, "a table is a data structure used to organize information." Langraff Decl., Separate Appendix, vol. 7, p. 1221. Notably, HP concedes that "the configuration table must specify information that governs aspects of the interaction between the logical units of the storage system and the host computing systems connected to the storage system." HP's Opening Brief, pp. 39-40.

At the same time, EMC's proposal is too narrow. While certain data relating to logical units obviously are contained within the configuration table, nothing in the claim language or the specification requires limiting the configuration table to a certain internal organization ("a table organized on a logical unit by-logical unit basis").

Accordingly, the Court construes this term as "a structure organizing data that governs the interactions

between logical units and host computing systems."

2. "host mode"

HP asks the Court to construe this term as: "An operational state that facilitates communication with a particular host." EMC proposes: "A mode, unique to a particular operating system, that specifies the manner in which an array controller should communicate with a host computer that is running said operating system."

Although the meaning of "host mode" is unclear from the claim language alone, a "host mode entry," according to the Court's construction of the preceding term, must be "data that governs the interactions between logical units and host computing systems." Indeed, according to the claim, a "host mode entry" may indicate "if a particular logical unit should communicate with a particular host computing system" and the host mode is predetermined.

For clarification, the Court must turn to the specification, which describes embodiments in which the host mode relates to the host's operating system. For example, "unique host 'modes' [are] adapted to be employed uniquely to each host operating system to which the logical unit ... is coupled. These unique host modes permit the array controller to be adaptable to handle different idiosyncrasies of particular host operating systems." '979:4/31-36. Although in one embodiment the host mode field "corresponds to the name of the operating system running on the particular host," '979:7/37-38, the host mode entry need not be limited to data concerning only a particular host or operating system. "For example, if a particular host is found to operate more efficiently or more smoothly in a particular mode, then based on the host operating system type, [such information can be] stored in the configuration table." '979:6/45-51. That is, although host mode entries contain information related to idiosyncrasies of a particular host, nothing in the intrinsic evidence requires each host to have a distinct or unique idiosyncrasy or associated host mode entry. Groups of hosts could share the same idiosyncrasy or host mode entry. Thus, a host mode entry could contain information about a particular operating system or the "operating system type."

The specification does not limit host mode entries solely to information relating to operating systems or operating system types. For example, the configuration table may include a data field such as "any special host modes for the particular host adapter." '979:5/11-12. The "host's adapter connects to the array controller." '979:5/41-42. This adapter contains identification information of the host, which is stored in the configuration table. '979:5/42-45. In this way, access to of the host to the logical units can be controlled. Thus, "host mode" data are additional information about the host, such as any of its "idiosyncrasies," '979:6/42-51-and not only the host's operating system.

Accordingly, a "host mode entry" may be an entry of data documenting the particular or idiosyncratic characteristics or the operational state of a host or group of hosts. This is consistent with a dictionary definition of "mode" as an "operational state of a computer or a program." Landgraff Decl., Separate Appendix, vol. 7, p. 1219 (Microsoft Computer Dictionary). Such information may be used in accordance with the invention to facilitate communication with a particular host (part of HP's proposal) or to specify the manner in which an array controller should communicate with a host computer (part of EMC's proposal). It follows that the term "host mode" relates only to the state of the host, not the purpose or use of the "host mode" data. Indeed, HP concedes that a "mode" is an "operational state of a computer." HP's Opening Brief, p. 40.

Accordingly, the Court construes this term as "the particular or idiosyncratic operational state of a host or group of hosts."

H. Disputed terms of the '801 patent.

The text of claim 1 FN5 is set forth below with the key disputed terms highlighted in bold type.

FN5. Although the Court refers to representative claims 1 and 20, it will construe the terms as used throughout the patent.

In a computer system including a processor and a peripheral device, the processor executing an application program which interacts With [sic] the peripheral device by sending peripheral device requests to operating system routines which send corresponding peripheral device commands to the peripheral device in response to the peripheral device requests, wherein the peripheral device is capable of replacing resident **microcode** with new **microcode** by download by the application program, and comprises:
a non-volatile memory containing the resident **microcode**;

circuitry for receiving peripheral device commands sent by the operating system in response to peripheral device requests from the application program; and

a resident processor, coupled to the non-volatile memory and receiving circuitry, and responsive to the resident **microcode**, comprising:

a detector of an **initiator peripheral device command** from the operating system corresponding to an initiator peripheral device request from the application program;

a detector of a **transfer peripheral device command** from the operating system corresponding to a transfer peripheral device request from the application program including the new **microcode**, received while in a **waiting state**; and

circuitry, responsive to the initiator command detector and the transfer command detector, for entering the **waiting state** when an **initiator peripheral device command** is detected, and for transferring the new **microcode** from the receiving circuitry into the non-volatile memory and restarting the operation of the peripheral device when a **transfer peripheral device command** is detected.

The text of claim 20 is set forth below with the key disputed terms highlighted in bold type.

A method of operating a peripheral device responsive to peripheral device commands corresponding to peripheral device requests from an application program, to replace resident **microcode** with new **microcode** by download comprising the steps of:

responding to an **initiator peripheral device command**, corresponding to an initiator peripheral device request by the application program, by entering a **waiting state** ready to receive new **microcode**; and

if in the **waiting state**, responding to a **transfer peripheral device command**, including the new **microcode**, corresponding to a transfer peripheral device request by the application program, by replacing

the resident **microcode** with the new **microcode** and restarting the operation of the peripheral device.

1. "microcode"

EMC asks the Court to construe this term as: "One or more programs for a peripheral device that can be stored in the non-volatile memory of the peripheral device." HP initially proposed: "Program instructions embedded in the internal circuitry of a microprocessor." Thus, the parties initially disputed where the microcode is stored. However, HP changed its proposal in its opposition brief to: "Program instructions that directly control a microprocessor, stored in internal circuitry that is non-volatile memory directly connected to that microprocessor." FN6 HP thus concedes that the microcode need not be stored in the microprocessor. Plaintiffs' and Counterclaim Defendants' Opposition Claim Construction Brief on Key Terms, p. 11.

FN6. EMC has filed a "Motion to Preclude HP from Asserting New Claim Construction Positions in its Opposition Brief." The Court has considered the motion on a term-by-term basis. Whether the motion should be granted or additional briefing from EMC is appropriate in light of the belatedness of HP's proposals depends upon whether EMC has had fair opportunity to present its position. The Court is satisfied that EMC had such an opportunity given the length and thoroughness of the hearing. Moreover, because claim construction is not only a matter of resolving disputes between litigants but also has a potentially preclusive effect with respect to litigation involving litigants not party to the present suit, the Court will consider HP's new positions to the extent that they assist the Court in construing the claim terms properly. Accordingly, the motion will be denied. For the sake of brevity, the Court generally will not restate HP's initial proposals. For the initial proposals see EMC's reply brief.

The claims do not define microcode; they merely indicate that microcode resides in non-volatile memory and may be replaced. The specification, however, provides useful insight. Peripheral devices have "special processors installed in them, called resident processors." '801:1/14-15. "These resident processors execute programs, called microcode in the remainder of this application, which are generally stored in a non-volatile memory in the peripheral device." '801:1/16-19. Thus, in its most general sense, "microcode" is a program executed by a peripheral device's resident processor. The remainder of the specification is consistent with this interpretation. *See, e.g.*, '801:2/33-35 ("resident processor ... is responsive to the resident microcode"), 2/50-57, 5/47-51, 6/35-37, & 7/46-48.

Although the disputed claims do not include the limitation of "control," HP proposes that microcode "controls" the peripheral device. HP is correct in implying that "microcode" does not include all possible types of computer code or programs. Indeed, the patent itself is entitled "Method and Apparatus for Replacing Resident Peripheral Device Control Microcode ...," and the written description nearly always modifies "microcode" with the word "control." EMC does not necessarily dispute that microcode is a limited subset of all possible computer programs or code: it concedes that microcode is a program "for a peripheral device," that is, code used to assist a peripheral device in functioning. The specification uses the word "microcode" in a manner consistent with this interpretation. *See, e.g.*, '801:1/25-29 ("In order to upgrade performance of, or provide new features for, such peripheral devices, the control microcode may be updated via a download of new control microcode."), 5/47-50 ("The resident processor 106 operates in a known manner, according to a control program stored in the control microcode in the non-volatile memory 108, to execute the disk control command."). Similarly, a dictionary definition provided by both parties defines microcode in part as the "lowest-level instructions that directly control a microprocessor." Declaration of Mark R. Weinstein in Support of EMC's Opening Claim Construction Brief, Ex. 3 (Random House

Webster's Computer & Internet Dictionary). While the Court will not import the word "control" into the claim, it notes that a person of ordinary skill in the art would understand "microcode" to mean a limited set of programs that are used specifically *for* a peripheral device.

With respect to the parties' contentions regarding the location of the microcode, it is true that microcode generally is stored in non-volatile memory in a peripheral device. However, "microcode" need not be defined according to its location, and nothing in the claim indicates that such a limitation must be added. Moreover, the importation of such a limitation would be inconsistent with the written description. For example, microcode sometimes is transferred from a central computer system for replacement purposes. *See* '801:1/26-29.

Similarly, nothing in the claim language or specification requires the microcode to control a microprocessor "directly" or that the non-volatile memory be "directly" connected to a resident microprocessor. Although microcode sometimes may "control" a resident processor, *see* '801:4/21-23, it is unclear what is meant by "direct" connection or control. The purpose of claim construction is to clarify the claim language, not to add ambiguous terms. Moreover, the invention appears to teach away from "direct connection" of the resident microprocessor and the non-volatile memory. *See* '801:Figure 1. Accordingly, the Court construes this term as "one or more programs for a peripheral device that can be stored in the non-volatile memory of the peripheral device and executed by a peripheral device's resident processor."

2. "waiting state"

EMC asks the Court to construe this term as: "State of operation of the peripheral device wherein the peripheral device is ready to receive new microcode." HP proposes (in its opposition brief): "A state in which a peripheral device stands ready to receive new microcode." The parties concede that their constructions are the same. Transcript of April 5, 2004 Hearing, 82:3-4; 87:12-16.

The meaning of "waiting state" is unclear from the claim language. The claim indicates that a detector of transfer peripheral device command receives the command and new microcode while in a waiting state and that there is circuitry for entering the waiting state in response to the initiator and transfer command detectors. The specification states:

When an initiator command is detected, a waiting state is entered in which the peripheral device is held ready to receive new microcode. The resident processor also includes a detector for a transfer peripheral device command, which includes the new microcode, received while the peripheral device is in the waiting state.

'801:2/36-42; *see also* '801:2/53 & 6/39-44. Thus, the "waiting state" is equivalent to the state of the peripheral device when it is ready to receive new microcode. Accordingly, the Court construes this term as "a state of the peripheral device in which it is ready to receive new microcode."

3. "initiator peripheral device command"

EMC asks the Court to construe this term as: "A command that signals to the peripheral device the beginning of the process of replacing resident microcode." EMC also is willing to add the following to its proposal: "This command is sent by the operating system to a peripheral device in response to an initiator peripheral device request sent by an application program to the operating system, and causes the peripheral device to enter a waiting state ready to receive new microcode." HP proposes (in its opposition brief):

A command sent by the operating system to a peripheral device in response to an initiator peripheral device request sent by an application program to the operating system. The command causes the peripheral device to enter a waiting state ready to receive new microcode. The command is separate and functionally different from a subsequently received transfer peripheral device command.

The initiator peripheral device command is one that an operating system sends to the peripheral device in response to a routine legitimately called by an application program (*e.g.*, a write or read request), as opposed to a special command for the peripheral device to which an application program would not normally have access.

Although the claim language does not clearly define the term, it indicates that the peripheral device enters the waiting period in response to the initiator peripheral device command. Additionally, the initiator peripheral device command corresponds to an initiator peripheral device request sent from the application program-executed by the computer system processor-to the operating system routine. The written description further explains:

The operating system provides operating system routines, legitimately accessible to an application program, for providing such access. In response to a call by an application program to such an operating system routine, the operating system will send a specific peripheral device control command ... to the peripheral device to perform the requested access.

'801:2/4-10.

It is not clear from the claim language whether the transfer and initiator commands must be "separate and functionally different." The claim language indicates that the peripheral device enters a waiting state in response to the initiator peripheral device command and that transfer of microcode to the peripheral device cannot occur in the absence of a transfer peripheral device command, strongly suggesting that there are two distinct commands. The claim does not state that microcode may be transferred in response to the initiator peripheral device command or that the transfer peripheral device command can induce a waiting state. Thus, it appears from the claim language alone that the two commands are distinct. The specification strongly suggests that the transfer and initiator commands must be different commands. For example, the resident processor of the peripheral device

detect[s] a first disk control command, called the initiator command ..., in response to which the disk drive is placed in a state waiting to receive new control microcode. When in this waiting state, a second disk control command, called the transfer command ..., is detected which contains the new control microcode for the disk drive.

'801:6/37-44. Similarly, "[w]hen the initiator command is detected, no transfer of data is performed to the disk drive platters 114. Instead, the disk drive enters a state ready to receive new microcode." '801:8/63-65. Finally, the prosecution history indicates that the patentee distinguished the invention from prior art that disclosed a "system which enters the waiting state when a single ... command containing the complete replacement microcode is being received and processed," and the patentee referred to the present invention as using a "two command sequence ... to download replacement microcode." Declaration of Steven E. Derringer in Support of Plaintiffss and Counterclaim Defendants' Opposition Claim Construction Brief on Key Terms ("Derringer Decl."), Separate Appendix, vol. 1, pp. 0170, 0174-75. The patentee's description is

consistent with the claim language and the specification. Accordingly, in the claimed invention, the peripheral device must receive two distinct commands in order to receive microcode.

HP also proposes language excluding a "special command." The basis for the limitation is found in the prosecution history, in which the patentee distinguished the claimed invention from the prior art by stating that it allowed for updating of resident microcode via operating system routine, in contrast to special commands that would require shutting down the computer system. This statement is consistent with a construction that includes reference to operating system routines that respond to application programs, in that a special command, by definition, does not utilize this process. *See* Derringer Decl., Separate Appendix, Vol. 1, p.App. 0170 (The "operating system forbids access to [special] commands by the application program."). Thus, the inclusion of reference to "special commands" is unnecessary.

Accordingly, the Court construes this term as "a command sent by the operating system to a peripheral device in response to an initiator peripheral device request sent by an application program to the operating system, and which causes the peripheral device to enter a waiting state ready to receive new microcode."

4. "transfer peripheral device command"

EMC asks the Court to construe this term as: "A command that transfers new microcode to the peripheral device." FN6 HP proposes (in its opposition brief):

FN6. EMC stated at the Claim Construction Hearing on April 5, 2004, that it is willing to add language similar to the language added for the prior term. Transcript of April 5, 2004 Hearing, 88:21-24. Obviously, EMC did not intend to adopt the exact language, and thus the Court must alter it so that it is consistent with the meaning of this term. The Court assumes, only for the purposes of assisting in the discussion, that EMC intended to add the following to its proposal: "This command is sent by the operating system to a peripheral device in response to a transfer peripheral device request sent by an application program to the operating system, and causes the peripheral device to receive new microcode."

A command sent by the operating system to a peripheral device in response to a transfer peripheral device request sent by an application program to the operating system. The command is received by the peripheral device while the device is in a waiting state, and it causes the peripheral device to download new microcode. The command is separate and functionally different from a previously received initiator peripheral device command.

The transfer peripheral device command is one that an operating system sends to the peripheral device in response to a routine legitimately called by an application program (*e.g.*, a write or read request), as opposed to a special command for the peripheral device to which an application program would not normally have access.

Although the claim language does not clearly define the term, it indicates, consistent with the specification, that the peripheral device receives the transfer peripheral device command while it is in the waiting state. The new microcode is transferred to the peripheral device when it detects the transfer peripheral device command. Additionally, the transfer peripheral device command corresponds to a transfer peripheral device request sent from the application program-executed by the computer system processor-to the operating system routine. The written description further explains:

The operating system provides operating system routines, legitimately accessible to an application program, for providing such access. In response to a call by an application program to such an operating system routine, the operating system will send a specific peripheral device control command ... to the peripheral device to perform the requested access.

'801:2/4-10.

HP's proposal includes reference to the initiator peripheral device command. As discussed above, the prosecution history indicates that the patentee intended to claim an invention that uses a "two command sequence ... to download replacement microcode." Deringer Decl., Separate Appendix, vol. 1, pp. 0170, 0174-75. This interpretation is consistent with the claim language and the specification, both of which describe a sequence of actions through which the peripheral device may receive microcode. That is, the peripheral device cannot receive microcode as part of the transfer peripheral device command prior to entering the waiting state in response to an initiator peripheral device command. HP also proposes language excluding a "special command." As stated above, a construction that includes access by an application program necessarily precludes the possibility of special commands.

Accordingly, the Court construes this term as "a command received by a peripheral device-after it has entered the waiting state in response to the initiator peripheral device command-from an operating system in response to a transfer peripheral device request sent by an application program to the operating system, and which causes the peripheral device to receive new microcode."

I. Disputed terms of claim 1 of the '497 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.

A method for identifying members of a logical set of mass storage devices, comprising the steps of:

defining a **global identifier** for said logical set which serves as a reference for identifying mass storage devices included in said logical set;

assigning **membership signatures** to a plurality of mass storage devices, wherein said **membership signatures** comprise information substantially matching said **global identifier** which identifies said plurality of mass storage devices as members of said logical set; and

when a member of said logical set undergoes a **change in membership status**, defining a new **global identifier** for said logical set different from said **global identifier** which thereafter serves as a reference for identifying members of said logical set, and assigning new **membership signatures** to other ones of said plurality of mass storage devices that remain members of said logical set, wherein said new **membership signatures** comprise different information substantially matching said new **global identifier** which identifies said other ones of said plurality of mass storage devices as members of said logical set.

1. "global identifier"

EMC asks the Court to construe this term as: "A 'global identifier' identifies the mass storage devices in a logical set." HP proposes (in its opposition brief and at the claim construction hearing, *see* Transcript of April 6, 2004 Hearing, 151:14-22): "A value or data structure stored in the array controller that is compared to membership signatures in order to identify which mass storage devices are members of a logical set of

mass storage devices ." Essentially, then, the parties dispute whether the term has a location limitation.

The meaning of "global identifier" can be ascertained from the claim language, which indicates that a "global identifier" serves as a reference for identifying mass storage devices included in a logical set. HP incorrectly argues that this is not a definition of "global identifier" but instead describes a *use* of a "global identifier." The construction in fact is a definition: the global identifier is a reference with which each storage device in a logic set identifies. In other words, knowledge of the global identifier allows the system to identify members of the set.

Nothing in the intrinsic evidence indicates that this term must be defined in part according to its location, nor is the term defined according to a process or method of comparing it to something else or according to its purpose. Accordingly, HP's proposed limitation requiring that the global identifier be stored in the array controller is inappropriate.

The Court construes this term as "a reference for identifying mass storage devices included in a logical set."

2. "membership signatures"

EMC asks the Court to construe this term as: "Information which identifies a mass storage device as a member of a logical set and substantially matching the global identifier." HP proposes (in its opposition brief and at the claim construction hearing, *see* Transcript of April 6, 2004 Hearing, 161:3-10): "A value or data structure stored either in the array controller or on the mass storage device, reflecting the device's status as an active member of a logical set of mass storage devices by substantially matching the global identifier."

The claim language indicates that membership signatures comprise information substantially matching the global identifier. The specification indicates that a membership signature is assigned "to each of the physical mass storage devices in the set [and it] identifies the physical mass storage device as a member of the set." '497:2/41-44. The set may be a logical set comprised of portions of the physical disk drives. *See* '497:3/12-16. Additionally, "[t]he signatures for all members are identical, or at least substantially identical (e.g., the signature may include a member number that differs from drive to drive)." '497:3/16-19.

HP's proposed additional limitations are not supported by the intrinsic evidence. The patentee expressly claimed a location limitation in dependent claim 8, strongly suggesting in light of the doctrine of claim differentiation that there is no location limitation in the independent claim. Moreover, nothing in the claim supports the importation of a limitation requiring the comparison of the global identifier to the membership signature in order to determine whether its status is "active." Instead, the members of a set are assigned membership signatures and the set is given a substantially matching global identifier.

Accordingly, the Court construes "membership signatures" as "information that identifies physical mass storage devices or portions of physical mass storage devices as members of a set and which substantially matches the global identifier of the set."

3. "change in membership status"

EMC asks the Court to construe this term as either: "change in membership status" or "a change in status resulting from an act affecting the member, such as the member being removed from the set." HP proposes (in its opposition brief): "Exclusion of a physical mass storage device from a logical set of mass storage devices (and, in certain circumstances, the writing of data onto the remaining physical mass storage devices

in the logical set) and updating the membership of the remaining physical mass storage devices in the logical set."

The claim language indicates that when there is a change in membership status, "other ones of said plurality of mass storage devices that remain members of said logical set" are assigned new membership signatures and the set is assigned a new substantially matching global identifier. The specification states that "[w]hen a member of the set undergoes a change in membership status the [sic] (e.g., removal of a physical mass storage device), a new membership signature is assigned to each remaining physical mass storage device in the set." '497:2/45-49. Thus, removal is only one possibility of status change. Indeed, the written description states: "whenever *any event* occurs to change the membership of any of the drives in the set" '497:3/20-22 (emphasis added). Removal or addition of a storage device occurs in the preferred embodiment. '497:2/23-26. Finally, dependent claim 2 limits the change in membership status to "the removal of said member from said logical set." Importing that limitation into independent claim 1 would render claim 2 superfluous. The Court therefore will not import "exclusion of a storage device" into the construction of this term. Similarly, there is nothing in the claim that requires writing data onto or updating the membership of the remaining members of the storage memory devices in the set (a limitation that appears to be the subject of claim 5). Although such acts may result from a change in membership, they are not necessary to a definition of the term.

Accordingly, the Court construes "change in membership" as "a change in status resulting from an act affecting a member of the set, such as a member being added or removed from the set."

J. Disputed terms of claims 1 and 13 of the '184 patent.

The text of claim 1 is set forth below with the key disputed term highlighted in bold type.

In a digital data processing system including at least one **local digital data processing system**, each said at least one local system including processor means for processing data items in response to instructions, a universal addressing system for addressing said data items comprising:

- (1) universal logical memory means accessible to each said at least one local system for storing and providing said data items,
- (2) memory organization means for organizing said universal memory means into objects uniquely and permanently identified by unique identifiers, each said data item being associated with a said object and addressable by means of a logical address specifying the unique identifier for said object with which said data item is associated and an offset specifying the locations of said data item in said associated object
- (3) means in said processor means for providing memory operation specifiers in response to said instructions, said memory operation specifiers each including a logical address and a memory command specifying a memory operation, and
- (4) memory operation means responsive to a memory operation specifier for accessing the data item and performing the memory operation specified by the memory command in said memory operation specifier on the data item specified by the logical address in said memory operation specifier.

The text of claim 13 is set forth below with the key disputed terms highlighted in bold type.

A digital data processing system comprising:

(1) universal logical memory means for storing and providing items of data including instructions,

(2) **memory organization means for organizing said universal logical memory means into objects uniquely and permanently identified by unique identifiers**, each said data item being associated with a said object and addressable by means of a logical address specifying the unique identifier of the object with which said data item is associated and an offset specifying the location of said data item in said associated object, and [sic]

(3) at least one **local digital data processing system** having access to said universal logical memory means and including processor means for processing said data items and providing memory operation specifiers in response to said instructions, said memory operation specifiers each including a logical address and a memory command specifying a memory operation, and

(4) memory operation means responsive to a memory operation specifier for accessing the data item and performing the memory operation specified by the memory command on the data item specified by said logical address.

1. "local digital data processing system"

EMC asks the Court to construe this term as: "A digital processing system (*i.e.*, a computer system) restricted to a particular area." HP proposes (in its opposition brief): "A computer system comprising a processor that is directly connected to a main memory and an input/output system."

The claim language indicates that the local digital data processing system is part of a digital data processing system and that it includes a processor for processing data. Although the term does not appear in the written description, the specification does discuss a "local system," *see, e.g.*, '184:abstract, which appears to be synonymous with the term. "The digital computer system in which the present invention is employed includes at least one local system including a processor and a universal memory accessible to the local system for storing data including instructions." '184:2/67-3/3. Thus, as described in the specification, the digital computer system is comprised of a universal memory and local digital computer systems that can access that universal memory. The claims acknowledge this view with additional limitations ("universal logical memory means accessible to each said at least one local system" and "local digital data processing system having access to said universal logical memory means"). The claims also include a limitation requiring the local digital processing system to include a "processor means." These limitations would be redundant if they formed part of the construction of the term.

The claim language requires "at least one" local system. However, it is instructive to refer to the '5602 patent, which is incorporated by reference, to understand the purpose of including "local systems." That patent describes an advantage of the invention as

providing a flexible internal system structure capable of performing multiple, concurrent operations, comprising a plurality of separate, independent processors, each having a separate microinstruction control and at least one separation and independent port of a central, independent communications and memory processor comprised of a plurality of independent processors capable of performing multiple, concurrent

memory and communications operations.

'602:4/3-11. Thus, the purpose of having "local" systems is that there could be multiple "local" systems. While claims 1 and 13 specifically include the possibility of having a single such system, it is the nature of a "local system" that there is the possibility of more than one distinct system. Accordingly, the word "local" signifies that the invention may include multiple, discretely located, and distinct systems.

Finally, nothing in the specification or claims of this patent or the '5602 patent requires a processor to be "directly connected to a main memory and an input/output system." These proposed limitations are part of a described embodiment. Moreover, it is unclear what "directly" connected to would mean in the context of the claim.

Accordingly, the Court construes this term as "a digital data processing system restricted to a particular area and physically and logically distinct from any other local digital data processing system if one exists."

2. "memory organization means for organizing said universal logical memory means into objects uniquely and permanently identified by unique identifiers"

EMC argues that despite the use of the word "means" this is not a means plus function claim, and it therefore asks the Court to construe this term as: "Memory organization means organizes the memory, which can include disk drives, into objects." Alternatively, should the Court construe the claim as a means plus function claim, EMC contends that the function of "memory organization means" is "organizing universal memory means into objects uniquely and permanently identified by unique identifiers" and its corresponding structure is "an object management system." HP proposes (in its opposition brief): "A means for organizing (i.e., arranging in a desired pattern or structure) universal memory means into objects uniquely and permanently identified by unique identifiers, having structures that are the same as or substantially equivalent to the Object Management System described in U.S. Patent No. 4,455,602 at Col. 20:32-21:16, Col. 49:60-Col. 51:5, Col. 62:10-Col. 64:52, Col. 356:64-Col. 364:45, Col. 367:45-Col. 369:7, and all corresponding figures including but not limited to Figure 2, Figure 101, Figure 106, Figure 106A and Figure 107."

The Court agrees with HP that this is a means plus function claim. The claim clearly states a function: "organizing said universal logical memory means into objects uniquely and permanently identified by unique identifiers." There is no clearly recited structure, material, or act in the claim for performing this function. Thus the Court must look to the specification for disclosed structure, material, or acts that are clearly linked or associated with this function. Further complicating the matter, the function includes reference to another "means": the "universal logical memory means." This refers to the preceding subparagraph, which states that the function of the "universal logical memory means" is "storing and providing said data items."

Because the '184 specification does not provide corresponding structure, material, or acts, the Court must look to the '5602 patent, which was incorporated by reference. The Federal Circuit, in *Atmel Corp. v. Info. Storage Devices, Inc.*, 198 F.3d 1374 (Fed.Cir.1999), held that a patentee may use sources that were incorporated by reference to define the disclosed structure, material, or acts of a means plus function claim if a person having ordinary skill in the art would do so. Nonetheless, "Paragraph 6 does not contemplate the kind of open-ended reference to extrinsic works that para. 1, the enablement provision, does." *Id.* at 1382. Thus, the '5602 patent disclosure only can be used to help define the structure, material, or acts disclosed in the '184 patent if a person having ordinary skill in the art would use that disclosure to help define the

structure, material, or acts. Moreover, to "incorporate material by reference, the host document must identify with detailed particularity what specific material it incorporates and clearly indicate where that material is found in the various documents." *Advanced Display Sys., Inc. v. Kent State Univ.*, 212 F.3d 1272 (Fed.Cir.2000). The '184 patent clearly indicates expressly that the entire '5602 patent is incorporated by reference.

The "universal logical memory means" is shown as MEM 112 in Figures 1 and 18 and is described at Column 36, line 42 through Column 38, line 41. It also is shown, more specifically, as MEM 10112 in Figure 101. In particular, "MEM 112 is an intelligent, prioritizing memory." '5602:36/52. "Major elements of MEM 112 are Main Store Bank (MSB) 1810, a Bank Controller (BC) 1814, a Memory Cache (MC 1816), a Field Interface Unit (FIU) 1820, and Memory Interface Controller (MIC) 1822." '5602:36/45-49. MSB 1810 "is comprised of one or more Memory Array Cards (MAs) 1812" of various capacity. '5602:37/13-14 & 37/22-23. "MC 1816 includes a bypass write path" and a "cache write-back path." '5602:37/55 & 37/58. Data transfer between internal components and to and from external components occurs through buses. *See, e.g.*, '5602:38/12-27. MEM 10112 may use "a single, large memory" or "physically separate memories." '5602:53/62 & 53/65-66. MEM 10112 is "structured into frames." *See, e.g.*, '5602:63/56-57.

The parties agree that the corresponding structure of the "memory organization means for organizing said universal logical memory means into objects uniquely and permanently identified by unique identifiers" is an "object management system." HP, however, seeks to define this term further by reference to the specific embodiments disclosed in the '5602 patent. The Court agrees that "object management system" is insufficient description of structure, material, or act to define this term. The specification describes the system in more detail in various places. For example, Figure 2 shows the organization of MEM 112. The figure is described in column 20: information stored on MEM 112 is organized into "Objects," each of which "is uniquely identified by a serial number referred to as a Unique Identifier (UID)." '5602:20/52-54. "UIDs provide an addressing base common to all CS 101 systems which may ever exist, through which any Object ever created may be permanently and uniquely identified." '5602:20/60-63. "[I]nformation within MEM 112 is located through MEM 112 Physical Addresses identifying particular locations within MEM112's memory space." '5602:21/44-47; *see also* '5602:50/38 & 53/17. Physical Addresses contain a "Frame Number (FN) field, a Displacement (D) field, and a Length (L) field. Together the Frame Number field and the Displacement field specify the location in MEM 112 containing the data, and the Length field specifies the length of the data." '5602:32/54-58 & Fig. 12.

Although the specification provides a more detailed description, a sufficient definition of structure, material, or acts necessary to perform the claimed function can be determined from this description alone. Moreover, this description, while providing sufficient corresponding structure, is general enough to avoid rendering the independent claims redundant. *See, e.g.*, *Wenger Mfg., Inc. v. Coating Mach. Sys., Inc.*, 239 F.3d 1225, 1234 (Fed.Cir.2001).

Accordingly, the Court construes this term as follows: The function is: "organizing said universal logical memory means into objects uniquely and permanently identified by unique identifiers." The corresponding structure, material, or act is: "The act of storing information into a universal logical memory means as described on page 48, line 21 through page 49, line 4 of this Order, in which information is organized by an Object Management System as described on page 49, line 10 through page 49, line 21 of this Order ."

K. Disputed terms of claim 1 of the '756 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.

A method for automatically **recovering** a computer system following discovery of a fault condition, comprising the steps of:

providing a computer system having self-testing and self-diagnosing capability;

automatically testing the computer system; automatically identifying the presence of one or more faulted components from said step of testing; and

de-configuring the computer system to functionally remove the faulted component from the computer system as identified by said step of automatically identifying.

1. "**de-configuring the computer system**"

EMC asks the Court to construe this term as: "Arranging the computer system such that the faulted component is functionally removed from the system." HP proposes (in its opposition brief): "Functionally removing a non-redundant faulted component from the computer system such that the function performed by the faulted component is not replaced. De-configuring the computer system does not include the step of replacing the faulted component or the functionality performed by the faulted component with a redundant component or with equivalent functionality."

Nothing in the claim language indicates that only a "non-redundant" component or functionality is removed, and HP's attempt to limit this term on the basis of the prosecution history is unsupported by the record. The inventors did not state that only "non-redundant" components are removed. Rather, in the cited portion of the prosecution history, they stated that in the claimed invention "a faulted component is not replaced by another redundant component nor is the system re-configured." Derringer Decl., Separate Appendix, vol. IX, p. 2611 (file history to U.S. Pat. No. 6,122,756).

The claim language indicates that one result of "de-configuring the computer system" is the removal of the identified faulted component from the computer system. Nothing in the claim language indicates that the component or its functionality is not replaced, although it is true that such replacement is not expressly claimed. Assuming for the sake of argument that the inventor disclaimed a "re-configuration" limitation in the course of prosecution, such an event would lead the Court only to omit such a limitation from protection by the claim at issue. It would not result in defining the "de-configuration" step by reference to a lack of "re-configuration." The claim simply does not refer in any way to replacement of functionality or components.

Accordingly, the Court construes this term as "functionally removing a faulted component from the computer system."

2. "**recovering**"

EMC argues that this term cannot be read as a limitation because it is in the preamble. Alternatively it asks the Court to construe the term as either: "recovering" or "restoring a system, program, database, or other system resource to a prior state following a failure or externally caused disaster." HP proposes: "The act of resetting a system or data stored in a system to an operable state following damage, including rebooting the computer system, the operating system and application program(s)."

The preamble indicates that a computer system is automatically recovered after discovery of a faulted component. The body of the claim provides the steps for "recovering," and, in so doing, it also indicates that a faulted component is automatically removed from a computer system.

It is well settled that if the body of the claim sets out the complete invention, and the preamble is not necessary to give life, meaning and vitality to the claim, then the preamble is of no significance to claim construction because it cannot be said to constitute or explain a claim limitation.

Schumer v. Lab. Computer Sys., Inc., 308 F.3d 1304, 1310 (Fed.Cir.2002). The preamble is redundant. The body of the claim provides that the system automatically discovers any faulted components and removes them after doing so. Accordingly, the Court declines to construe this term.

L. Disputed terms of the '347 patent.

The text of claim 1 is set forth below with the key disputed terms highlighted in bold type.FN7

FN7. Although the Court refers to representative claim 1, it will construe the terms as used throughout the patent.

A system for automatically providing and maintaining data, said system comprising:
a host computer located in a first geographic location;

a first data storage system located in a first geographic location and coupled to said host computer, for storing data to be accessed by at least said host computer;

a second data storage system located in a second geographic location geographically remote from said first location, coupled to said first data storage system, for receiving at least data from said first data storage system; and

said first data storage system enabling transfer of said data to said second data storage system, concurrently with said data received from said host computer, so as to nearly simultaneously maintain a concurrent copy of data stored on said first data storage system and on said second data storage system wherein both said first and said second data storage systems **maintain an index**, said index including at least a first **indicator** providing an indication of whether a predetermined data element stored on said first data storage system is valid, and at least a second **indicator** providing an indication of whether said predetermined data element stored on said second data storage system is valid.

1. "indicator"

EMC asks the Court to construe this term as:

Information which provides a fairly certain sign or symptom of the validity of a predetermined data element. An indicator can include information about data located on a storage device, such as a track, or about data stored in an entire storage device via a device-level indicator. The requisite first and second indicators may be organized at different levels so long as the second provides information with respect to the validity of the same predetermined data element as the first even if that information is provided indirectly.

HP proposes: "An 'indicator' is something that 'indicates,' which means points out or points to, or states or expresses briefly, with certainty."

HP's proposal is an everyday definition of the word, except for the fact that it includes the requirement of "certainty." EMC proposes a construction that would limit the term to the "validity of a predetermined data element," but, instead of requiring "certainty," would require only an "indication" that is "fairly certain." The claim language states that an "indicator" provides an indication of whether a predetermined data element stored on a first or second data storage system is valid, thus supporting EMC's proposed "predetermined data element" limitation. However, that limitation stands on its own and need not be included in the Court's specific construction of the term "indicator."

The claim language does not help to resolve the parties' dispute over the level of certainty required. Indeed, nothing in the claim language explicitly limits the term to "indicates with certainty." The word "indicate," by itself, does not necessarily require certainty; in fact, HP's addition of modifying words suggests that it seeks a particularly narrow construction. The dictionary definition of "indicate" does not include "certainty." ("Indicate" means "to point out or point to," or "to be a sign, symptom, or index of." Webster's Ninth New Collegiate Dictionary.)

Nor is there a requirement of certainty in the specification, which uses the term "indicator" according to its common meaning. For example, the "secondary data storage system controller provides an indication or acknowledgement [sic] to the primary data storage system controller that the primary data to be copied to the secondary data storage system in identical form as secondary data has been received or ... written." '347:2/63-3/1. The invention is able to "achieve[] nearly 100 percent data integrity." '347:2/34-35. The "indicators" also indicate several measures of "validity." There are indications of "write or copy pending ... of both the primary data ... and the secondary data," '347:7/46-47, "pending format change," '347:7/48, and the validity of data storage location, '347:8/10-12. There are also "indicators" of whether a primary or secondary device may be written to and whether a primary and secondary track is not shown. '347:8/23-24 & 8/36. In none of these discussions of the various indicators is there a suggestion or requirement that the indicator indicate with certainty. Such a requirement likely would be a highly significant limitation and improvement, as very few (and possibly no) computer systems ever function with absolute certainty.

Accordingly, the Court construes "indicator" as "something that 'indicates,' which means points out or points to, or to be a sign, symptom, or index of."

2. "maintain an index"

EMC argues that this term should be given its plain and ordinary meaning. Alternatively it asks the Court to construe it as: "Keep or store an index." HP proposes: "To keep an index in an existing, up-to-date state (as of repair, efficiency or validity)." HP thus seeks to include a limitation requiring the index to be kept in an "up-to-date state."

It is unclear what "up-to-date-state" would mean in the context of the claim. It is true that the claim indicates that the index is modified with use. For example, the claim language suggests that the index is updated as the storage systems store new data: the

storage systems maintain an index, said index including at least a first indicator providing an indication of

whether a predetermined data element stored on said first data storage system is valid, and at least a second indicator providing an indication of whether said predetermined data element stored on said second data storage system is valid.

However, the claim language does not specify *when* the index is updated.

Similarly, although several portions of the written description suggest that the index is updated, the specification provides no basis for the "up-to-date-state" limitation, nor does it provide guidance as to what such language would mean. For example, the storage system controller "maintaining a list of primary data to be copied updates this list to reflect that the given primary data has been received by and/or copied to the secondary data storage system." ' 347:3/20-23.

[S]ince data will not be immediately synchronized between the primary and secondary data storage systems, data integrity must be maintained by maintaining an index or list of various criteria including a list of data which has not been mirrored or copied, data storage locations for which a reformat operation is pending, a list of invalid data storage device locations or tracks, whether a given device is ready, or whether a device is write-disabled. Information must also be included as to the time of the last operation so that the data may later by synchronized should an error be detected.

'347:7/22-32. Moreover, "[w]hen the primary data storage system controller disk adapter writes the data to the primary data storage device, it will reset bit 104 of the write pending indicator bits." '347:7/59-62. Thus, although the specification describes a system in which indices are updated as part of the data storage on both systems, it does not include a requirement as to when such updating must or should occur. Under these circumstances, importation of a limitation requiring the index to be kept in an "up-to-date-state" could exclude the claimed invention itself if the invention's indices were not updated *instantaneously*.

In the absence of contrary language in the specification, a person having ordinary skill in the art would understand this term to have its plain meaning. A dictionary definition-consistent with the description of the claimed invention-of "maintain" is "to keep in an existing state (as of repair, efficiency, or validity)." Webster's Ninth New Collegiate Dictionary. According to the plain meaning of the term, the index must be kept in a state of proper use as defined by the claim. The claim indicates that the index contains information concerning the validity of predetermined data elements. Thus, because the index generally must represent the existing states of the storage systems, it must be updated at some point after the validity of predetermined storage elements is altered.

Accordingly, the Court construes this term as "keeping-although not necessarily instantaneously-an index in a state of validity."

IT IS SO ORDERED.

Produced by Sans Paper, LLC.